



ENGINEERED TO PREVENT
CONDENSATION

ArmaFlex Class 1

Built-in water vapour barrier to reduce
risk of corrosion under insulation.

- // Class 1 fire classification according to BS476 Part 7
- // Minimise long-term heat gain and reduce energy cost
- // Closed-cell structure increases resistance to water vapour



 **armacell**[®]
ArmaFlex[®]

ENGINEERED TO PREVENT CONDENSATION

ArmaFlex Class 1

Built-in water vapour barrier to reduce risk of corrosion under insulation (CUI). Conserves energy and reduces heat loss. Class 1 fire classification according to BS476 Part 7. Certified by leading international fire safety agencies. Fibre-free.

Easy to install



Prevent condensation



Reliable performance



// Closed-cell structure

Minimises moisture permeation to ensure long-term protection against corrosion under insulation. Removes the need for an additional water vapour barrier.

// Good fire performance

FM Approved for entire range of insulation thickness. Certified to conform to safety, reliability and performance standards of various local fire safety bodies.

// Energy efficient

Low thermal conductivity minimises energy losses to give long term energy savings.

// Environmentally safe

Zero Ozone Depletion Potential and Global Warming Potential; rated "Excellent" by Singapore Green Building Council.

// Safer indoor air quality

Free of fibre and formaldehyde, and GREENGUARD® Gold certified for low emissions of volatile organic compounds.

// Easy-to-install

Highly flexible elastomeric foam that can be installed quickly on irregular shapes and installations in tight spaces.



TECHNICAL DATA - ARMAFLEX CLASS 1

Brief description	ArmaFlex Class 1 is a flexible insulation material that reliably protects against water vapour ingress due to its closed-cell structure. No additional water vapour barrier is required.
Material type	Flexible elastomeric foam based on synthetic rubber (NBR).
Product colour range	Black
Special features	Engineered wall: increasing insulation wall thickness for tubes ensures that the surface temperature is maintained as the pipe diameter is increased.
Applications	Thermal insulation/protection of pipes, air ducts and vessels (incl. elbows, fittings, flanges etc.) in air conditioning, refrigeration and process equipment to prevent condensation and to save energy. Structure-borne noise reduction in service-water and waste-water installations.
Installation	Please refer to the ArmaFlex application manual for advice. ArmaFlex can be used together with ArmaFlex 520 adhesive and ArmaFix pipe hangers for a complete insulation system.

Property	Value / Assessment				Standard / Test method
Temperature range					
Service temperature	Min. °C		Max. °C		
	-50		105		
	Remarks		+85 °C if sheet is glued to the object with its whole surface.		
Thermal conductivity					
Declared thermal conductivity	Øm	-20 °C	0 °C	25°C	GB/T 10295, GB/T 10296, ASTM C518, EN ISO 8497
	λd ≤ [W/(m·K)]	0.032	0.034	0.036	
Fire Performance and Approvals					
Surface spread of flame	Class 1				BS 476 Part 7
FM approved	Yes				FM 4924
Flammability					
Flammability of plastic materials	V-0 rating				UL 94
Fire performance					
Practical fire behaviour	Does not generate flaming droplets.				
Others	Product conforms to requirements for building products under the Fire Safety and Shelter Department of Singapore.				
Resistance to water vapour					
Water vapour diffusion resistance factor	μ ≥ 10,000				GB/T 17146, EN 12086, EN 13469
Water vapour permeability	≤ 1.96 x 10 ⁻¹¹ g/(m·s·Pa)				GB/T 17146, EN 12086, EN 13469
Resistance to water					
Water absorption by vacuum	≤ 0.5% by volume				GB/T 17794
Mechanical properties					
Resilience after compression relief	≥ 70%				GB/T 6669
Weather and UV resistance					
UV resistance	For UV protection, ArmaFinish Paint or Arma-Chek® covering system is required. For outside use, ArmaFlex should be protected within three days of installation.				

Property	Value / Assessment	Standard / Test method
Health and environment		
Health aspects	Free of fibre and formaldehyde. Low Volatile Organic Compounds (VOC), low total aldehyde. GREENGUARD Gold for even lower VOC and total chemical emissions.	UL 2818
Environmental aspects	Zero ODP and GWP.	
Environmental Product Declaration (EPD)	Type III EPD: Declaration number 4789125188.101.1, UL Environment.	
Green building assessment	Singapore Green Building Product Certified: "Excellent" rating.	
Other technical features		
Chemical resistance	Please consult product test list.	
Shelf life	Self-adhesive sheets, tubes and tapes: 1 year	
Storage	Material shall be stored in dry, clean rooms at normal relative humidity (50% to 70%) and ambient temperature (0°C to 35 °C).	

Adhesives and Cleaners

Item	Description	Content [quantity]
AS-AD5201E	4 cans of 1 Gallon (3.78litres) ArmaFlex 520 adhesive in a carton	4 tin
AS-AD520HL	12 cans of 500mL ArmaFlex 520 adhesive in a carton	12 tin

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. Despite taking every precaution to ensure that said data and technical information are up to date, Armacell does not make any representation or warranty, express or implied, as to the accuracy, content or completeness of said data and technical information. Armacell also does not assume any liability towards any person resulting from the use of said data or technical information. Armacell reserves the right to revoke, modify or amend this document at any moment. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. This document does not constitute nor is part of a legal offer to sell or to contract.

At Armacell, your trust means everything to us, so we want to let you know your rights and make it easier for you to understand what information we collect and why we collect it. If you would like to find out about our processing of your data, please visit our Data Protection Policy.

Trademarks followed by © or ™ are trademarks of the Armacell Group. © Armacell, 2024. All rights reserved.

ArmaFlex | ArmaFlex Class 1 | Brochure | 062024 | en-VN

ABOUT ARMACELL

As the inventor of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With more than 3,300 employees and 25 production plants in 19 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for acoustic and lightweight applications, recycled PET products, next-generation aerogel technology and passive fire protection systems.



For more information, please visit:
www.armacell.com